








HEAR NO EVIL

VAN DAMME PRO GRADE CLASSIC XKE INSTRUMENT CABLE



Van Damme Pro Grade Classic XKE Instrument Cable is a relatively low capacitance unbalanced audio cable for use with guitars, keyboards and other unbalanced output devices. Its tight construction and dual screens of conductive thermoplastic and close lapped copper ensure noise free handling and excellent noise rejection making this cable ideal for on stage use.

KEY BENEFITS		MATERIALS			APPLICATIONS	
						
Multiple Colours	Flexibility	Oxygen Free Copper	Flexible PVC	Silver-plated oxygen-free copper	Bands & Guitarists	Live Sound

HEAR NO EVIL

Applications

- Guitar cables
- Keyboard and sound module cables
- Hi-Fi interconnects

Application Notes

- Low noise and high flexibility for on stage use
- Multiple colours for application or length colour coding
- Dual thermoplastic/lapped copper screens for excellent noise rejection
- Combination of silver plated and plain ultra-pure oxygen free copper conductors for unsurpassed sound quality

Mechanical Specification

Conductors	3 x 0.20 mm silver plated ultra-pure oxygen-free copper 4 x 0.20 mm bare ultra-pure oxygen-free copper
Conductor size	7 x 0.20 mm, 0.22 mm ² , AWG 24/7
Insulation	Foamed polyethylene
Screen 1	0.40 mm conductive thermoplastic
Screen 2	80 x 0.10 mm close lap spiral bare oxygen-free copper
Jacket material	Flexible PVC/Neoprene composite
Overall diameter	6.00 ± 0.15 mm
Bend radius	10 x overall diameter
Operating temperature	-20 to +70 °C

Electrical Specification

Resistance	Conductor	< 90 Ohm/km
	Insulation	> 5000 MOhm/km
Capacitance	Core to screen	90 pF/m



HEAR NO EVIL

Part Numbers and Description

Part Number	Description	RAL Code	Reel Lengths
268-011-000	Van Damme Pro Grade Classic XKE Instrument jet black	RAL 9005	100 m, 300 m
268-012-060	Van Damme Pro Grade Classic XKE Instrument ultramarine blue	RAL 5002	100 m, 300 m
268-013-020	Van Damme Pro Grade Classic XKE Instrument traffic red	RAL 3020	100 m, 300 m
268-072-050	Van Damme Pro Grade Classic XKE Instrument mint green	RAL 6029	100 m, 300 m
268-084-080	Van Damme Pro Grade Classic XKE Instrument squirrel grey	RAL 7000	100 m, 300 m
268-074-040	Van Damme Pro Grade Classic XKE Instrument sulphur yellow	RAL 1016	100 m, 300 m
268-076-090	Van Damme Pro Grade Classic XKE Instrument traffic white	RAL 9016	100 m, 300 m
268-078-030	Van Damme Pro Grade Classic XKE Instrument bright orange	RAL 2007	100 m, 300 m
268-082-010	Van Damme Pro Grade Classic XKE Instrument nut brown	RAL 8011	100 m, 300 m
268-080-070	Van Damme Pro Grade Classic XKE Instrument signal violet	RAL 4008	100 m, 300 m

Standards and Compliance

RoHS 2011/65/EU Restriction of Hazardous Substances

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals