



THE ROUTE OF LEAST RESISTANCE

SEE NO EVIL

VAN DAMME ENHANCED PERFORMANCE UHD VISION 12GHZ 0.7/2.9 COAXIAL CABLE



APPLICATIONS



Broadcast



Video



Presentations

MATERIALS



Oxygen free
copper



Skin Foam Skin
Polyethylene



Flexible PVC

KEY BENEFITS



Precision 75
Ohm Impedance



Extended
Transmission
Length

A new addition to the Van Damme UHD coaxial range, this 4.50mm diameter coaxial is ideal for shorter 4K/UHD cable runs and rack build applications. As with the RG6 type, 268-875-006, its precision construction ensures that electrical performance is optimised, ensuring trouble free performance with 4K Single-link 12 Gb/s UHDTV, SMPTE 424M and 292M HDSDI signals as well as SDI and analogue video.

www.van-damme.com

SEE NO EVIL

Applications

- Transmission of UHD, HD-SDI, SDI and analogue video signals
- SMPTE 2082-1 12 Gb/s UHD TV up to 45 metres
- SMPTE 2081-1 6 Gb/s UHD TV up to 65 metres
- Designed for installation, touring, outside broadcast and other dynamic uses

Application Notes

- Use of precision 75 Ohm components throughout any signal chain is imperative
- See downloads for further transmission length guidelines

Mechanical Specification

Conductor	Silver plated oxygen free copper
Stranding	1 x 0.70 mm
Size	0.38 mm ²
Dielectric	Gas injected foam skin polyethylene
Diameter (mm)	2.90
Screen 1	Aluminium/polyester foil (bonded) > 115%
Screen 2	Tinned oxygen free copper braid > 90%
Overall jacket	Flexible PVC Jet Black RAL 9005
Overall diameter (mm)	4.50 ± 0.20
Bend radius	10 x overall diameter
Operating temperature	-15 to +75 °C

Electrical Specification

Conductor resistance (Ohm/km)	46
Capacitance (pF/m)	56
Impedance (Ohms)	75 ± 3
Velocity ratio	> 78%
Attenuation (dB/100m)	
100 MHz	10.10
200 MHz	13.90
300 MHz	16.70
500 MHz	22.00
750 MHz	26.80
1500 MHz	39.10
3000 MHz	55.60
6000 MHz	81.00



SEE NO EVIL

Part Numbers and Description

Part Number	Description	Max. Reel Length
268-075-006	Van Damme 75ohm Enhanced UHD Vision 12GHz 0.7/2.9 coax	500 m

Recommended BNC Connectors

339-075-300	Van Damme 12G UHD BNC cable male Serial DV75 (SD Vision) Neutrik rearTWIST HD BNC NBNC75BFG7 Neutrik rearTWIST UHD BNC NBNC75BFG7X
-------------	--

Connector selection criteria:

Conductor	Dielectric diameter	Overall diameter	Summary
1 x 0.70 mm	2.90 mm	4.50 mm	(0.7/2.9/4.5)

Standards and Compliance

RoHS 3 (EU 2015/863)	Restriction of Hazardous Substances
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals